

Ref: (80) JPB/281-6/1 Vol. 6

tel: +607-2535 888 fax: +607-2510 980

15th March 2016

All Johor Port Berhad Dangerous Cargo Jetties (DCJ) Users

Dear Sir/Madam,

MANDATORY SAFETY REQUIREMENTS FOR ENTERING DANGEROUS CARGO JETTIES (DCJ) AREAS IN JOHOR PORT BERHAD (JPB).

The above subject matter is kindly referred.

As you are all fully aware that we are the OHSAS 1800:2007 international standard certified organization, which requires us to maintain and continuously improve on Occupational Safety and Health ("OSH") at our workplace within JPB premises.

It has been "JPB"'s culture that we practiced the ALARP (as far as practically practicable) to maintain the safety and wellness of port users within our premises at all time. Thereby I wish to remind all port users (staff, tenants and leases, customers, contractors, visitors, suppliers, government agencies, regulatory bodies and other stakeholders) that it is mandatory for ALL who enter JPB operations areas and workplace to observe and comply strictly to the safety rules and regulations.

I wish to remind any port users entering our DCJ (BT1, BT2, BT3, BT4, BT12 and CT3A) shall adhered to the followings mandatory safety requirements:

1. Declaration of entering DCJ at JPB's Security Post. Log book will be provided by JPB.
2. Usage of mobile phone is strictly prohibited except onboard of vessel (upon getting approval from vessel's captain).
3. Usage of camera is strictly prohibited except onboard of vessel (upon getting approval from vessel's captain). Any camera usage in the DCJ shall get the approval and permit from PSSD (Port Security & Safety Department) officer.
4. Usage of walkie-talkie is allowable for IS type (intrinsically safe / explosion proof).
5. Usage of personal protective equipment (PPE); safety shoe, safety helmet, long pants, long sleeve jacket and safety vest are mandatory. Safety vest is not required if the jacket is embedded with reflective sticker.
6. Usage of life jacket is mandatory when crossing the gangway to onboard vessel and also when crossing the life jacket boundary markings at jetties apron.
7. Usage of spark arrestor for any diesel & petrol engine-driven vehicle / equipment is mandatory. Spark arrestor must be constructed from stainless steel material and must be checked on schedule basis for any damages, cracked or dented.

JPB reserves the right to prohibit any entry to DCJ or take necessary action if found fail to comply with any requirements stipulated. Therefore your understanding, continuous support and usual co-operations are duly appreciated to ensure a safe working place and conducive environment for everyone.

Should you require further clarification, please liaise with Pn Siti Kamariah binti Md Shahrin at kamariah@johorport.com.my or our department Safety Health & Environment (SHE) representative accordingly.

*'Safety is Everybody's Responsibility'*Kind Regards,
JOHOR PORT BERHADMOHD AIMAN-DIANG ABDULLAH
General Manager,
Port Security and Safety Department